



Pall Corporation

PCM400 series portable cleanliness monitor

The Pall® PCM400 is specifically developed as a portable diagnostic monitoring device that provides an assessment of system fluid cleanliness.



PCM400 Cleanliness Monitor

Benefits

As part of continued component cleanliness 'pass off' checks or predictive maintenance programs the PCM400 monitor quickly reports test data so that ongoing assessments can be made.

Early detection of abnormal fluid cleanliness allows for timely investigation and corrective actions to be implemented.

The PCM400 can be permanently installed to monitor critical applications (including component test facilities) or used as a portable device for routine condition monitoring of various fluid systems.

Operation

A detachable hand held touch screen programmer allows for simple menu driven input of sample identification, monitor configuration and data output in either ISO4406, NAS 1638 or SAE AS 4059D formats.

The hand held programmers display shows real time data and test results which are automatically stored for subsequent trending and evaluation.

PCM400 monitor features


- Proven mesh blockage technology
- Results not affected by water or air
- Monitors dissolved water content (% saturation or PPM output for specific fluids (PCM400W only))
- High and low pressure on-line or off-line sampling
- Continuous monitoring
- 500 test memory
- ¼" BSP or test point hoseconnection
- PC-based trending software included
- Viscosity output in centistokes (cSt)
- Real time graphical representation

Applications

- Component wash fluids
- Cutting fluids
- Aqueous solutions
- Coolants
- Water glycols
- Mineral and synthetic oils
- Lubricants
- Fuels

Specifications

Power supply:	90-230VAC or integral 19 VDC battery
Temperature:	10°C to 80°C (50°F to 150°F)
Compatibility:	Water glycols, aqueous solutions. Petroleum and synthetic oils (hydraulic lubricating, dielectric, etc.) fuels, industrial phosphate esters.
Seals:	Fluorocarbon
Operating viscosity:	1.5 to 450 cSt
Pressure:	0 to 315 bar (4568 psi) max
Range:	ISO 4406: 10/8/6 to 21/19/16 NAS 1638: 2 to 10 @ 5-15 µm SAE AS 4059D:2B to 10B
Accuracy:	± 1/2 ISO code
Output:	RS232
Enclosure:	IP 65
Weight:	11 kg (24 lb)
Dimensions:	340 x 240 x 265 mm (14 x 10 x 10 inches)



PCMTrender software features

- Graphical and spreadsheet reporting
- Trending capabilities
- Customer defined alarm limits
- Printable reports

Ordering Information

Pall Part Number	Description
PCM400W	Portable Cleanliness Monitor with integrated water sensor for use with non-aqueous fluids (Petroleum based fluids, industrial phosphate esters, mineral/synthetic oils).
PCM400	Portable Cleanliness Monitor (without water sensor) for aqueous fluids (wash fluids @ pH<11.0, water glycols, cutting fluids)




Pall Corporation

Pall Machinery and Equipment
 Portsmouth - **UK**
 +44 (0)23 9230 3303 telephone
 +44 (0)23 9230 2507 fax
 m&e_sales@pall.com

New York - **USA**
 800 333 7255 toll free
 +1 516 484 5400 telephone
 +1 516 484 3825 fax

Because of developments in technology these data or procedures may be subject to change. Consequently we advise users to review their continuing validity annually. Part numbers quoted above are protected by the Copyright of Pall Europe Limited.

 and Pall are trade marks of Pall Corporation.
 Filtration. Separation. Solution is a service mark of Pall Corporation.
 ® indicates a trademark registered in the USA.
 ©2002, Pall Europe Limited.

Filtration. Separation. Solution.sm

Visit us on the web at www.pall.com/m&e

Pall Corporation has offices and plants throughout the world in locations including: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, Hong Kong, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, Mexico, the Netherlands, New Zealand, Norway, Poland, Puerto Rico, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, United States, and Venezuela. Distributors are located in all major industrial areas of the world.

Your distributor is: